

Compact Oil Mist Filters

EF Series 1/2" - 1 3/4"

Features

- Captures oil fog, mist or aerosol from discharge of oil sealed vacuum pumps
- Steel construction with nickel plated finish
- Seamless drawn housings
- Easy thumb screw access for element maintenance
- Oil run-off from the filter returns to the pump

Technical Specifications


- 0.3 micron media; 99.97% efficiency
- Continuous operating temp: 20°C (68°F) to 80°C (180°F)



Options

- Additional ISO flange connections
- Non-standard connection styles

Connection Size	Type	Assembly m ³ /hr Rating	Assembly Part Number	Dimensions - mm			Suggested Service ht. mm	Approx. Weight kg.	Replacement Element Part No.
				A	B	C			
1/2"	MPT	8	EF-FG5-050	102	23	64	76	0.3	FG5
1/2"	MPT	12	EF-FG7-050	127	23	64	102	0.8	FG7
3/4"	3/4-20 UNEF	7	EF-FG3-077	83	25	64	54	0.5	FG3
3/4"	MPT	8	EF-FG5-075	110	31	64	76	0.4	FG5
3/4"	MPT	12	EF-FG7-075	135	31	64	102	0.8	FG7
1"	1-20 UNEF	8	EF-FG5-103	100	21	64	76	0.3	FG5
1"	1-20 UNEF	12	EF-FG7-103	125	21	64	102	0.4	FG7
1"	1-20 UNEF	27	EF-FG9-103	130	23	129	102	0.8	FG9
1"	1-20 UNEF	41	EF-FG10-103	179	23	129	152	3.2	FG10
1 3/4"	1 3/4-20 UN	41	EF-FG10-177	208	52	129	152	1.6	FG10
16 mm	ISO Flange	8	EF-FG5-NW16	101	22	64	76	0.3	FG5
25 mm	ISO Flange	8	EF-FG5-NW2516	101	22	64	76	0.6	FG5
25 mm	ISO Flange	41	EF-FG10-KF25	211	54	129	152	1.6	FG10
40 mm	ISO Flange	75	EF-FG20-KF40	191	54	260	121	3.2	FG20



See Oil Mist Discharge Filter Technical Data for sizing guidelines.

Rev: EF-EU1909K

United Kingdom
Phone: +44 (0) 1902 798499
UKsales@solbergmfg.com

Belgium
Phone: +32 3 774 52 11
BEsales@solbergmfg.com

Germany
Phone: +49 9129 145 3902
vertrieb@solbergmfg.com

Slovakia
Phone: +421 (0) 48 41 33 251
predaj@solbergmfg.com

All model offerings and design parameters are subject to change without prior notice.
Contact your representative or Solberg for the most current information.

www.solbergmfg.com

Technical Data

Oil Mist Discharge Filters

Applications & Equipment

- Vacuum Pumps & Systems
- Vacuum Furnaces & Ovens
- Vacuum Freeze Drying & Outgassing
- Vacuum Metalizing
- Vacuum Drying
- Vacuum Coating
- Custom Vacuum Pumping Systems
- Food Processing & Packaging
- Industrial Vacuum Processes
- Pressure Unloading Vents on Piston Compressors
- Medical Work Areas
- Industrial Aerosol Scrubbing
- Heat Treating Equipment
- Vacuum Hold Down
- Routing Equipment
- Laboratory Industry
- Leak Detectors
- Autoclaving, Sterilization
- Reciprocating Engines
- Crankcase Ventilation Systems


Identification

Standard Solberg assemblies should have an identification label/nameplate that gives the following information:

- Assembly Model #
- Replacement Element #


The part number designates the filter type, the element configuration and housing connection size. For example, the following part number identifies the filter as being an “HDL” design filter with a “PSG344/2” coalescing element, and 3”BSPT connection size.

HDL-PSG344/2-301



Installation & Maintenance

Mounting orientation is typically top-up vertical so draining can occur. See figure below for proper installation method. Request appropriate maintenance manual from your Solberg representative or through www.solbergmfg.com.



Rev: OilMistTech-EU0719K

Oil Mist Discharge Filters

General

Recent developments in product design allow for the possible selection of oil mist discharge filters based on the type of equipment being used. It is now possible to identify the appropriate grade of aerosol discharge filter because of the extensive research completed by the Solberg R&D department. Please follow the rules below to correctly size your oil mist discharge filter. If further consultation is required, please contact Solberg or the Solberg sales representative in your area.

Filter Selection Guidelines

#1: First of all, air/oil separators used in compressed air systems repeatedly fail in vacuum pump applications. The first consideration is to determine the type of vacuum pump being used. The particle size distribution and mass of oil aerosol discharging from a vacuum pump is as varied as the number of separator tank designs utilized by the industry. The main pump types are rotary vane, rotary screw, rotary piston, liquid ring, and reciprocating vacuum pumps. Each type of pump produces its own specific oil discharge characteristics and requires the appropriate media make-up to effectively capture and drain oil aerosols.

#2: Determine the type of oil being used in the vacuum pump. Trade names, viscosity/grade of oil, and the lubricant base (mineral, synthetic, etc.) are all useful details for determining the discharge aerosol characteristics.

#3: Determine how much oil the pump consumes under normal operating conditions. Typical consumption rates are gallons or liters per hour. The amount of oil consumed is typically the amount of oil being discharged.

#4: Pump operating cycles including vacuum range, temperature fluctuations, contaminant gases or vapors, and hours of operation per day/week. Also, determine the maximum pressure drop or filter restriction that the system will allow.

#5: Determine the operating temperature at the discharge connection. If it is above +104°C, methods of cooling the aerosol should be considered.

#6: Note the horsepower of the pump, the outlet connection, and the air flow.

#7: When an external unit is to be used as the primary or sole air/oil separator in a system, a multi-stage severe duty system may be required.

#8: In the case where an existing air/oil separator (internal or external) is already used, it is important to specify the desired goal for a second filter. Is it planned to have a multi-staged system for severe or extreme duty applications, or is there a requirement for exceptionally clean discharge air? If a multiple stage system is needed, try to identify the primary stage unit and the purpose for the second stage.

#9: Consider where to install the filter. Where possible, it is best to install in moderate temperature (+2° to +38°C) environments and avoid freezing conditions to ensure the oil drains freely without causing undue back pressure to the vacuum pump.

Once as much information as possible has been obtained, send the data to Solberg for review, review our data sheets in the catalog, or visit our website at www.solbergmfg.com.



SOLBERG

www.solbergmfg.com

*All model offerings and design parameters are subject to change without prior notice.
Contact your representative or Solberg for the most current information.*