



DESCRIPTION

REV

A UPDATED STANDARD LAYOUT

10.50 [267 mm]				9.40 [239 mm] INTERNAL HEIGHT
.50 [13 mm]	4.8 [123	mm]———	SP	ONGE GASKET

ELEMENT SPECS					
PART NUMBER	239P				
MATERIAL	POLYESTER				
FLOW RATE	570 CFM	968 m³/hr			
SURFACE AREA	13.1 ft²	1.2 m ²			
I.D.	4.85"	123mm			
O.D.	9.22"	234mm			
HEIGHT	10.50"	267mm			
<u> </u>	·				

ECN # CHG BY DATE APP'D

12/03/19

NAD

TAS

17839



THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.**

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER PRO

MODEL NUMBER: 239P	SHEET
WODEL NOWBER. 2591	1 OF 1

DESCRIPTION: 239P, POLY

ROJECT:	DRAWN BY: EZR	APPROVED BY: TAS	REV
	DATE: 11/6/2018	DATE : 11/6/2018	Α