



EV	DESCRIPTION	ECN#	CHG BY	DATE	APP'D
Α	ADJUSTED ELEMENT SURFACE AREA	29995	WZL	06/28/24	GSS



ELEMENT SPECS					
PART NUMBER	244S2				
MATERIAL	SS WIREMESH				
FLOW RATE	880 CFM	1494 m³/hr			
SURFACE AREA	14.9 ft ²	1.4 m ²			
I.D.	6.00"	152mm			
O.D.	9.75"	248mm			
HEIGHT	9.70"	246mm			

REV:

s ^m i ®	SOLBERG® Filtration • Separation • Silencing 630.773.1363 • www.solbergmfg.com
-----------------------	--

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.**

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

MODEL NUMBER: 244S2	SHEET:
WODEL NOWBER. 24432	1 OF 1

DESCRIPTION: 244S2, WIREMESH, 316 SS, BROWN PLASTISOL, SPONGE

PROJECT:	DRAWN BY: RWK	APPROVED BY:
	DATE : 2/21/2019	DATE: