





ELEMENT SPECS				
PART NUMBER	34S			
MATERIAL	WIREMESH			
FLOW RATE	275 CFM	467 m³/hr		
SURFACE AREA	4.5 ft <sup>2</sup>	0.4 m <sup>2</sup>		
I.D.	4.75"	121mm		
O.D.	7.88"	200mm		
HEIGHT	4.84"	123mm		

Filtration • Separation • Silencing 630.773.1363 • www.solbergmfg.com		SOLBERG® Filtration • Separation • Silencing 630.773.1363 • www.solbergmfg.com
---	--	--

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS ELIBBILED IN DOUBLEST. WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

## **TOLERANCES**

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.** 

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

MODEL NUMBER: 34S	SHEET:
WODEL NOWDER. 340	1 OF 1

**DESCRIPTION:** 34S, WIREMESH

PROJECT:	DRAWN BY: AMM	APPROVED BY: JSR	RE
	<b>DATE</b> : 4/13/2020	<b>DATE</b> : 4/17/2020	