





ELEMENT SPECS				
PART NUMBER	484S2			
MATERIAL	316 SS WIREMESH			
FLOW RATE	4705 CFM	7994 m³/hr		
SURFACE AREA	71.9 ft <sup>2</sup>	6.7 m <sup>2</sup>		
I.D.	14.00"	356mm		
O.D.	19.63"	499mm		
HEIGHT	21.45"	545mm		



THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

## **TOLERANCES**

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.** 

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

MODEL NUMBER: 484S2	SHEET:
WIODEL NOWIDEN. 40432	1 OF 1

**DESCRIPTION:** 484S2, WIREMESH, 316 SS

PROJECT:	DRAWN BY: RWK	APPROVED BY: NAD	RE
	<b>DATE</b> : 10/15/2019	<b>DATE</b> : 10/16/2019	