









ELEMENT SPECS		
PART NUMBER	245P	
MATERIAL	Polyester	
FLOW RATE	880 CFM	1495 m³/hr
SURFACE AREA	14.0 ft <sup>2</sup>	1.3 m <sup>2</sup>
I.D.	6.00"	152mm
O.D.	9.75"	248mm
HEIGHT	9.63"	244mm

FINISH: BLACK POWDER

SHEET:

1 OF 1

**TOLERANCES** 

DIMENSIONS ARE FOR REFERENCE ONLY.

ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.** 

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL

AND THE PROPERTY OF SOLBERG MANUFACTURING INC.
AND IT IS FURNISHED TO YOU WITH THE EXPRESS

UNDERSTANDING THAT IT WILL NOT BE REPRODUCED,

COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR

USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT

WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE

RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

SD15876

MODEL #: CSL-245P-501

MODEL NUMBER: CSL-245P-501

**DESCRIPTION:** CSL-245P-501, BLACK

**APPROVED BY:** M.C. REV: PROJECT: **DRAWN BY:** CRW В **DATE:** 8/2/2010 **DATE:** 8/2/2010

MATERIAL: CARBON STEEL



**SOLBERG**® Filtration • Separation • Silencing 630.773.1363 • www.solbergmfg.com