



REV	DESCRIPTION	ECN#	CHG BY	DATE	APP'D
Α	UPDATED TO 3D, WEATHERHOOD WAS 16" OD	PRJ 474	JAM	12/12/17	NAD



	ELEMENT SPECS		
PART NUMBER	245P		
MATERIAL	Polyester		
FLOW RATE	880 CFM	1495 m³/hr	
SURFACE AREA	14.0 ft ²	1.3 m ²	
I.D.	6.00"	152mm	
O.D.	9.75"	248mm	
HEIGHT	9.63"	244mm	

FINISH: GRAY POWDER

	SOLBE Filtration • Separation 630.773.1363 • www.solk	ERG® • Silencing pergmfg.com
--	---	-------------------------------

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS ELIBBILED IN DOLL DECOLUSED. WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.**

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

MODEL NUMBER: F-245P-500	SHEET:
WODEL NUMBER: F-245P-300	1 OF 1

MATERIAL: CARBON STEEL

DESCRIPTION: F-245P-500, GRAY

MODEL #: F-245P-500

	PROJECT:	DRAWN BY: CRW	APPROVED BY: MJC	REV
SD118	SD11583	DATE : 9/7/2005	DATE : 9/7/2005	Α