









ELEMENT SPECS		
PART NUMBER	485P	
MATERIAL	POLYESTER	
FLOW RATE	4705 CFM	7994 m³/hr
SURFACE AREA	71.7 ft²	6.7 m ²
I.D.	14.00"	356mm
O.D.	19.63"	499mm
HEIGHT	21.45"	545mm
I.D. O.D.	14.00" 19.63"	356mm 499mm

MATERIAL: CARBON STEEL

FINISH: GRAY POWDER

SHEET:

1 OF 1

MODEL #: F-485P-DN250

DESCRIPTION: F-485P-DN250, GRAY

MODEL NUMBER: F-485P-DN250

WISE SPECIFIED:
N INCHES
PROJECT:

SOLBERG®
Filtration • Separation • Silencing
630.773.1363 • www.solbergmfg.com

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE UPON PRODUCTION.

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

TOLERANCES

 DRAWN BY:
 RWK
 APPROVED BY:
 TAS
 REV:

 DATE:
 2/1/2019
 DATE:
 2/4/2019
 A