





ELEMENT SPECS					
PART NUMBER	485P				
MATERIAL	Polyester				
FLOW RATE	4705 CFM	7994 m³/hr			
SURFACE AREA	71.7 ft ²	6.7 m ²			
I.D.	14.00"	356mm			
O.D.	19.63"	499mm			
HEIGHT	21.45"	545mm			

SOLBERG® Filtration • Separation • Silencing 630.773.1363 • www.solbergmfg.com

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.**

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

MODEL #: FS-485P(2)-1400F	MATERIAL: CARBON STEEL	FINISH: GRAY POWDER	
MODEL NUMBER: FS-485P(2)-1400F	.		SHEET : 1 OF 1

DESCRIPTION: FS-485P(2)-1400F, GRAY

REV: PROJECT: DRAWN BY: CRW **APPROVED BY:** A.A. **DATE:** 6/1/2005 **DATE:** 6/2/2005