


EV	DESCRIPTION	ECN#	CHG BY	DATE	APP'D
Α	UPDATED REMOVAL CLEARANCES	21357	JSR	03/02/21	TAS
В	UPDATED SHIPPING POSITION, ADDED NOTE 2	21628	LJS	04/06/21	JEB



	SLOT POSITION			DIM C	DIM D	
^	1	75.75 (1923mm)	17 (432mm)	84.25 (2139mm)	105.25 (2673mm)	
	2	69.75 (1771mm)	17 (432mm)	78.25 (1987mm)	99.25 (2521mm)	
	3 (DEFAULT)	63.75 (1619mm)	17 (432mm)	72.25 (1835mm)	93.25 (2369mm)	
	4	57.75 (1467mm)	17 (432mm)	66.25 (1683mm)	87.25 (2217mm)	
	5	51.75 (1315mm)	17 (432mm)	60.25 (1531mm)	81.25 (2065mm)	
B	6 (SHIPPING)	42.25 (1073mm)	17 (432mm)	50.75 (1289mm)	71.75 (1822mm)	

NOTES & SPECIFICATIONS:

1. LIQUID CAPACITY (HI GAUGE PORT CENTERLINE): 40 GAL.

2. CHECK THE MAINTENANCE MANUAL FOR SERVICE HEIGHT RECOMMENDATIONS.



THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC.
AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

ALL DIMENSIONS ARE SUBJECT TO CHANGE

UNLESS OTHERWISE SPECIFIED: -DIMENSIONS ARE IN INCHES -REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY -FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

DIMENSIONS ARE FOR REFERENCE ONLY. **UPON PRODUCTION.**

MODEL NUMBER:	KNOCKOUTDN250-METRIC
MODEL NUMBER:	KNOCKOU I DINZOU-IVIE I KIC

SHEET: 1 OF 1

MATERIAL: CARBON STEEL

DESCRIPTION: KNOCKOUTDN250, TANK, LEGS, SIGHT GLASSES, PLUGS, BALL VALVE, METRIC, RAL7036

PROJECT: **DRAWN BY:** JEB **APPROVED BY:** CRW

REV: В **DATE:** 2/8/2018 **DATE:** 2/8/2018

FINISH: RAL 7036