

Stamped Steel Filter Silencers

FS Series 1/4" - 1"

Features


- High grade filter element with integrated gasket seal
- Fully drawn weatherhood
- Tubular silencing design: tube maximizes attenuation and air flow while minimizing pressure drop
- Corrosive resistant black powder coat carbon steel
- Ability to mount vertically and horizontally

Technical Specifications

- Temp (continuous): min -26°C (-15°F) max 104°C (220°F)
- Filter change out differential: 37-50 mbar over initial ΔP
- Polyester: 99%+ removal efficiency standard to 10 micron
- Paper: 99%+ removal efficiency standard to 2 micron
- Pressure drop graphs available upon request

Options

- Various media for different environments
- Straight through configuration
- Various nonstandard finishes and connection styles



MPT Outlet	Assembly m ³ /hr Rating	Assembly Part Number		Dimensions (mm)			Suggested Service Ht. (mm)	No. of Silencing Tubes	Approx. Weight (kg)
		Polyester	Paper	A	B	C			
1/4"	7	FS-05-025	FS-04-025	70	17	63	51	1	0.11
3/8"	14	FS-05-038	FS-04-038	70	17	63	51	1	0.11
3/8"	14	FS-07-038	FS-06-038	91	17	81	51	1	0.23
1/2"	14	FS-05-050	FS-04-050	75	23	63	51	1	0.11
1/2"	20	FS-07-050	FS-06-050	96	23	81	51	1	0.23
1/2"	20	FS-11-050	FS-10-050	106	23	105	51	1	0.45
3/4"	20	FS-07-075	FS-06-075	105	31	81	51	1	0.23
3/4"	43	FS-11-075	FS-10-075	114	31	105	51	1	0.45
1"	60	FS-11-100	FS-10-100	114	31	105	51	1	0.45

Learn More

For more information about Solberg products and finding the right solutions for your equipment needs, visit us at **SolbergMfg.com**.