





NOTES & SPECIFICATIONS:

1. UNIT RATED FOR 100 - 200 SCFM (170 - 340 m³/hr).



THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.**

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

MODEL #: ST-SML345-400C	MATERIAL: CAST ALUMINUM/PLASTIC	FINISH: NONE	
MODEL NUMBER: ST-SML345-400C			SHEET: 1 OF 1
DECORPTION: CT CMI 245 400C OLEAD DUCKET			

| DESCRIPTION: ST-SML345-400C, CLEAR BUCKET

PROJECT:

APPROVED BY: NAD **DRAWN BY:** TAS **DATE:** 3/31/2020 **DATE:** 4/1/2020

REV: