





NOTES & SPECIFICATIONS:

MODEL #: WL-825-NW16EN

- 1. FLANGES TO BE PROTECTED DURING PRODUCTION & SHIPMENT.
- 2. UNIT TO BE HELIUM LEAK TESTED TO 1 x 10-5 mbar L/s.

ELEMENT SPECS				
PART NUMBER	825			
MATERIAL	POLYESTER			
FLOW RATE	25 CFM	42 m³/hr		
SURFACE AREA	0.3 ft ²	0.0 m ²		
I.D.	1.50"	38mm		
O.D.	2.54"	65mm		
HEIGHT	2.66"	68mm		

FINISH: ELECTROLESS NICKEL

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE

RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.**

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

MODEL NUMBER:	WL-825-NW16EN	SHEET:
		1 OF 1

MATERIAL: CARBON STEEL

DESCRIPTION: WL-825-NW16EN, ELECTROLESS NICKEL

PROJECT:	DRAWN BY: RWK	APPROVED BY: EZR	RE
	DATE: 8/20/2019	DATE : 8/21/2019	

